

hanatek



www.hanatekinstruments.com

FST Film Shrink Tester

- Stretch film
- Blown film
- Shrink wrap

Hanatek products are exclusively
manufactured and distributed by

 **RHOPOINT**
INSTRUMENTS

FST Film Shrink Tester

The Hanatek FST is used to measure the effect of temperature on plastic films.

The application of heat causes certain plastic films to rapidly contract; this effect can be used to seal and pack many items from food to consumer goods.

The shrink effect is due to internal forces locked into the film during manufacture being released by heating, it is also known as linear thermal shrink or free shrink.


The amount of shrinkage is dependent on the film type, thickness and sealing temperature.

Testing the percentage shrink of a film ensures that it is suitable for a particular packaging application and establishes the correct temperature for that application.

APPLICATIONS



Stretch film



Blown film



Shrink wrap

FEATURES

Fast efficient testing

Fast and accurate hotplate control allows film shrink tests to be performed in minutes.

Easy determination of percentage film shrink

The easy to read, back lit scale allows percentage shrink to be easily determined.

ACCESSORIES

- High temperature oil
- Template
- Pipette
- Tweezers
- Cutting knife



FST SPECIFICATIONS

Standards	ASTM D 2732-03
Display	LCD with set point and actual temperature reading
Temperature	Range 40-400° C Accuracy +/- 0.3° C
Timer	Lapse timer with alarm, registers overshoot
Size	(H)120 x (W)300 x (D)270mm
Weight	4.7kg
Packed Weight	6.1kg
Commodity Code	9027 8045 60



Certificate No. FM29741
ISO: 9001-2008



LOCAL AGENT

hanatek

12 Beeching Road | Bexhill-on-Sea | East Sussex | TN39 3LG | UK
Tel: +44 (0) 1424 739623 | Fax: +44 (0) 1424 730600
sales@hanatekinstruments.com | www.hanatekinstruments.com